

# D6115

## Digital Conference System Host



### *Description*

This system has comprehensive functions and can use different operation modes to manage conference discussions according to different requirements of users. It can be used in conjunction with simultaneous interpretation and wired/wireless language distribution systems.

The system can be connected to a computer for operation, or it can work independently from the computer. The system control mode is selected on the host panel: computer control mode and host control mode. The host power is 115W, a single host can support 60 delegate / chairman mics, and a single host plus extended host can support communication capacity up to 240 mics.

## *Features*

- The host and the conference mics are connected via the 8-pin cable for digital control and sound signal transmission.
- Can be operated independently or with an external computer combined with software for synchronous linkage operation to realize a variety of conference management functions (conference mode or operation: designated speech, free speech, application speech and first-in first-out speech, etc.)
- Standalone machine can realize the following conference functions: free mode, limit mode, first-in first-out mode.
- With good sound quality channel effect.
- With three conference management modes:
  - Free mode (Free )
  - First-in first-out (FIFO)
  - Limited speech (LIMIT)
- Can choose the number of speaking mics at the same time from 1-9 (inclusive) or free-mode speech.
- With the external video central processor, it can realize the function of speaker positioning and tracking.
- With LCD on the panel, 122×32 dot matrix display of conference mode. With function keys and knobs on the panel for system settings and adjustment.
- With audio signal output terminal, it can be connected with the recording or audio equipment.
- With the connection terminal for the telephone coupler, it can be connected with the telephone coupler for telephone conference.
- Frequency response: 40HZ~16KHZ; THD: <0.1%.
- Power consumption: 115W.
- Power supply: AC220V-240V, 50Hz-60Hz.
- Comply with international conference equipment and international safety standards UL, and CE certification.
- Net weight: 11.8kg.
- Outer dimensions (W×H×D): 485mm (including handles) × 100mm (2U, including chassis foot pad) × 355mm; can be placed horizontally on the table or installed in a 19-inch standard cabinet.

## *Specifications*

Model	D6115
LCD	122×32 dot matrix display
Frequency Response	40HZ~16KHZ
THD	<0.1%
Power consumption	115W
Power Supply	AC220V-240V, 50Hz-60Hz
Outer dimensions (W×H×D)	485mm (including handles) × 100mm (2U, including chassis foot pad) × 355mm
Net Weight	11.8kg